

GUILD HALL, PRESTON

TECHNICAL SPECIFICATIONS

Technical: Guild Hall

Stage Dimensions: 18290mm W x 7620mm D x 735mm H
(6 sections, 2 of 3810mm x 10970mm, 4 of 3810mm x 3810mm)

Power: 3 phase: 60, 100, 150, 300 amps

Rigging: Various rigging points rated @ 1 ton (See attached plan)
Please be aware of acoustic canopy above stage area.

LIGHTING

Lighting control: Avolites Pearl expert (Strand 520i available at request – shared resource)

Followspots: 2 x Lycian Starklite II followspots

Advanced truss: 24 x par cans, 6 x Junior Source Four Zoom (S4's are shared resource and available at request)

Rear Truss: 24 x par cans

Top Gantry

11 X 2K Fresnels (On fixed catwalk)

6 X 2K Profiles (on fixed catwalk).

N.B. these will not focus on stage when the front truss is at working height.

6 X Source 4 Pars

8 X Short nosed Par 64 floor cans

We do not carry a large stock of gel, and cannot guarantee exact colours. We will endeavour to meet your requirements with adequate notification. (Lee colours used)

SOUND

Recently installed NEXO GEO S line array.

GUILD HALL PA SPECIFICATION

MAIN LEFT AND RIGHT HANGS: (PER SIDE) 5 X NEXO GEOS 805 HIGH MID CABINETS

1 X NEXO GEOS 830 HIGH MID CABINET

3 X NEXO GEOS BASS CABINETS

SIDE FILLS: (MONO SUM OF L & R) (PER SIDE) 4 X NEXO GEOS 805 HIGH MID CABINETS

1 X NEXO GEOS 830 HIGH MID CABINET

OPTIONAL CENTRE FILL: ALSO MONO SUM 1 X NEXO GEOS 805 MID HIGH CABINET

1 X NEXO GEOS 830 MID HIGH CABINET

ALL ABOVE RUNNING ON DEDICATED NEXO NX242 CONTROLLERS + BSS SOUNDWEB DSP+ CAMCO AMPLIFIERS. SYSTEM TIME ALIGNED BASS TO MID HIGH. GLOBAL DELAY CAN BE ALTERED TO SUIT.

AT PRESENT SYTEM CAPABLE OF 4 WAY PASSIVE STAGE MONITOR MIX

MONITORS ARE ADLIB AUDIO 600W 4ohm BOXES, POWERED BY QSC RMX 2450 AMPLIFIERS.

FRONT OF HOUSE CONTROL:

DESK: YAMAHA LS 9/32

GRAPHICS: BSS FCS 966 31 BAND CONSTANT Q OPALS

SOURCE:

2 X TASCAM CDA500 CD/CASSETTE

1 X TASCAM MD350 MINIDISC

1 X MARANTZ ST6001 TUNER

MULTICORE: 1 X 48 WAY MULTI HARDWIRED TO CONTROL ROOM
(ON STAGE) 2 X 10M VEAM TO 12 WAY XLR STAGE BOXES
2 X 20M VEAM TO 12 WAY XLR STAGE BOXES
1 X 48 WAY VEAM TO MONITOR BREAK OUT (XLR)
1 X 48 WAY RECORD BREAKOUT (XLR)

MICROPHONES: VARIOUS MICS

A SMALL SELCTION OF MICROPHONE STANDS

Lift Access: Goods Lift from ground to all floors.

Size 2745mmD X 2080mmW X 2285mmH. Door width 1880mmW.

Parking: Available for up to 3 large vehicles (Trucks or Coaches) in Lord street loading area.
Vehicles should reverse into this area from Lancaster road end.

Twin 13A power available.

Additional parking may be available on nearby bus station, by prior arrangement, and at additional cost.

Personal vehicles should be parked in nearby multi-storey car park.

Please Note

The loading area also serves as fire access and escape for retail units within the complex. Access to these units should be maintained at all times. Please advise drivers to park on the yellow hatched markings nearest to the road, and not immediately next to the building.